Mallinckrodt™

SAFETY DATA SHEET

1. Identification

Product identifier INOmax®

Other means of identification

SDS number NO123

Synonyms Nitric Oxide (<2.3%) Blended with Nitrogen * INOflo® * INOcal®

Recommended use Pharmaceutical grade nitric oxide for inhalation balanced in nitrogen. Nitric oxide is a pulmonary

vasodilator and the active substance in these products. The gaseous blend of nitric oxide and nitrogen gas is supplied in aluminum cylinders as a compressed gas. INOcal is used in the

calibration of medical devices.

Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name Mallinckrodt Manufacturing LLC

Address 1060 Allendale Drive

Port Allen, LA 70767

Supplier

Company name Ikaria Canada Inc.

Address 6345 Dixie Road, Unit 1

Mississauga Ontario ON L5T 2E6 Canada

Telephone number 877-566-9466.

Emergency telephone

number

1-800-424-9300 (CHEMTREC)/ 703-527-3887

Supplier Not available.

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas

Simple asphyxiants Category 1
Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Specific target organ toxicity, repeated Category 2 (blood)

exposure

Environmental hazards Not classified.

Label elements

Health hazards



Signal word Warning

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye

irritation. May cause damage to organs (blood) through prolonged or repeated exposure. May

displace oxygen and cause rapid suffocation.

Material name: INOmax® SDS CANADA

SDS ID: NO123 Version #: 02 Revision date: 11-11-2016

Precautionary statement

Prevention Do not breathe gas. Keep container tightly closed. Wash thoroughly after handling. Wear

protective gloves. Wear respiratory protection. Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Storage Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Those with pre-existing heart, lung, or blood disorders may be more susceptible to the symptoms of asphyxia.

Nitric oxide converts to nitrogen dioxide when exposed to air.

Federal law prohibits dispensing without a prescription. Used in the treatment of prescribed medical disorders. Administration of this gas mixture may be hazardous or contraindicated. Use only under the supervision of an experienced licensed practitioner familiar with the indications for

use, dosages, methods, hazards, contraindications, and side effects.

Supplemental information

Mixtures

None.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
NITROGEN	Nitrogen; Nitrogen NF; LIN; Cryogenic Liquid Nitrogen; Refrigerated Liquid Nitrogen	7727-37-9	>=97.7
NITRIC OXIDE		10102-43-9	<=2.3
Composition comments	All concentrations are in percent by weight unless in percent by volume.	ngredient is a gas. Ga	s concentrations are in
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Get medical attention if symptoms persist.		
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.		
Ingestion	Rinse mouth. Never give anything by mouth to a vic convulsions. Do not induce vomiting. If vomiting occ doesn't get into the lungs. Get medical attention if s	curs, keep head low s	
Most important symptoms/effects, acute and delayed	Exposure to rapidly expanding gas or vaporizing liquirritation. May cause redness and pain. Dermatitis. Stinging, tearing, redness, swelling, and blurred vision blindness could result. Prolonged exposure may call	Severe eye irritation. Son. Permanent eye da	Symptoms may include

skin), numbness of the extremities, unconsciousness and death.

Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is

Continued exposure can lead to hypoxia (inadequate oxygen), cyanosis (bluish discoloration of the

Material name: INOmax® SDS CANADA

stopped.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Frostbite: Do not remove clothes, but flush with copious amounts of lukewarm water. Call an ambulance and continue to flush during transportation to hospital. Do not rub affected area.

If you feel unwell, seek medical advice (show the label where possible). In case of cold burns (frostbite) caused by rapidly expanding gas or vaporizing liquids, get medical attention promptly. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Use any media suitable for the surrounding fires. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Fire or excessive heat may result in rupture of container due to release of significant amounts of gases. Ruptured cylinders may rocket. During fire, gases hazardous to health may be formed such as: Nitrogen Oxides. Carbon oxides.

Special protective equipment and precautions for firefighters Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn

Specific methods General fire hazards Cool containers exposed to flames with water until well after the fire is out.

Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

In the event of a leak evacuate all personnel until ventilation can restore oxygen concentrations to safe levels. Keep away from sources of ignition - No smoking. Keep out of low areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Emergency personnel need self-contained breathing equipment. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop leak if you can do it without risk. Eliminate sources of ignition. Isolate area until gas has dispersed. Use water spray to reduce vapors or divert vapor cloud drift. Collect spillage. Transfer to a container for disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Handling and storage

Precautions for safe handling

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Always wear NIOSH approved, positive pressure air supplied respirator when handling this material. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Store in original tightly closed container. Protect against physical damage and/or friction. For storage condition, see finished product label. Store in a well-ventilated place. Protect from sunlight. Store away from incompatible materials (see Section 10 of the SDS).

Material name: INOmax® SDS CANADA

SDS ID: NO123 Version #: 02 Revision date: 11-11-2016

8. Exposure controls/personal protection

Occupational exposure limits

LIS	ACGIH	Threshol	d I imit	Values
UG.	AUGILI	1111631101	ч шин	values

Components	Туре	Value	
NITRIC OXIDE (CAS	TWA	25 ppm	
10102-43-9)			

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value
NITRIC OXIDE (CAS 10102-43-9)	TWA	31 mg/m3

25 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	
NITRIC OXIDE (CAS	TWA	25 ppm	
10102-43-9)			

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	
NITRIC OXIDE (CAS	TWA	25 ppm	
10102-43-9)			

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
NITRIC OXIDE (CAS	TWA	25 ppm	
10102-43-9)			

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	
NITRIC OXIDE (CAS 10102-43-9)	TWA	31 mg/m3	
		25 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Use explosion-proof equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Chemical goggles are recommended.

Skin protection

Hand protection Wear protective gloves. Thermally protective, chemical resistant gloves are recommended. If

contact with forearms is likely, wear gauntlet style gloves.

Other Wear suitable protective clothing.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved

respiratory protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Compressed gas.

Color Colorless - Nitric oxide can produce brownish nitrogen dioxide after reaction with oxygen.

Odorless in product concentration, may form NO2 with pungent odor in presence of air.

Odor threshold 0.5 - 5 ppm for NO2

pH Not available.

Melting point/freezing point -263 °F (-163.89 °C) @ 1 atm Initial boiling point and boiling -241 °F (-151.67 °C) @ 1 atm

range

Flash point Not flammable.

Evaporation rate Not available.

Flammability (solid, gas) Not flammable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not flammable.

(%)

Flammability limit - upper

Not flammable.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not applicable.

Vapor density 1.3 kg/l @ NTP (20 °C, 1atm)

Relative gas density = 1.04 @ NTP (20 °C, 1atm)

Solubility(ies)

Solubility (water) 7.4 ml/100 ml (NO in water at 0 °C)

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Not available.

Viscosity

Not applicable.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Contains gas under pressure; may explode if heated. Nitric oxide converts to nitrogen dioxide

when exposed to air.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Protect against direct sunlight. Avoid heat, sparks, open flames and other ignition sources. Avoid

high temperatures. Low temperatures. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases. Metals. Metal oxides.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Suffocation (asphyxiant) hazard - if allowed to accumulate to concentrations that reduce oxygen

below safe breathing levels.

Skin contact Causes skin irritation. May cause frostbite or freezing of skin.

Eye contact Causes serious eye irritation. Exposure to rapidly expanding gas or vaporizing liquid may cause

frostbite ("cold burn"). Permanent eye damage including blindness could result.

Ingestion Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn").

However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn"). Skin irritation. May cause redness and pain. Dermatitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Symptoms of overexposure can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting, and are reversible if exposure is stopped.

Continued exposure can lead to hypoxia (inadequate oxygen), cyanosis (bluish discoloration of the skin), numbness of the extremities, unconsciousness and death.

Information on toxicological effects

Acute toxicity May displace oxygen and cause rapid suffocation.

Components Species Test Results

NITRIC OXIDE (CAS 10102-43-9)

Acute

Inhalation

Gas

LC50 Rat 130 ppm, 4 hours LC50 Rat 115 ppm, 1 Hours

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Canada - British Columbia OELs: Simple asphyxiant

NITROGEN (CAS 7727-37-9) Simple asphyxiant.

Canada - Manitoba OELs Hazard: Asphyxiant

NITROGEN (CAS 7727-37-9) Simple asphyxiant.

Canada - Ontario OELs: Asphyxiant

NITROGEN (CAS 7727-37-9) Simple asphyxiant.

Canada - Quebec OELs: Asphyxiant

NITROGEN (CAS 7727-37-9) Simple asphyxiant.

Respiratory sensitizationDue to lack of data the classification is not possible. **Skin sensitization**Due to lack of data the classification is not possible.

Germ cell mutagenicity Nitric oxide has demonstrated genotoxicity in Salmonella (Ames Test), human lymphocytes, and

after in vivo exposure in rats.

Carcinogenicity Due to lack of data the classification is not possible. This product is not considered to be a

carcinogen by IARC, ACGIH, NTP, or OSHA.

Not carcinogenic at inhalation exposures up to 20 ppm in rats for 20 hr/day for up to 2 years.

Higher exposures have not been investigated.

Reproductive toxicity Due to lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

Due to lack of data the classification is not possible.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (blood) through prolonged or repeated exposure.

Aspiration hazard Due to lack of data the classification is not possible.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThis product has no known eco-toxicological effects. The nitric oxide component of this gas

mixture will react with air to form nitrogen dioxide, which in contact with water or moist air will form

nitrous and nitric acid.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

NITROGEN 0.67

Mobility in soil No data available.

Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. Disposal considerations

Disposal instructionsWaste containing this product is classified as Industrial Waste. Do not puncture, incinerate or

crush. Waste materials should not be released into the environment. Dispose of contents/container

in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Empty gas cylinders should be returned to the vendor for recycling or refilling. Empty containers

should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

TDG

UN number UN1956

UN proper shipping name Transport hazard class(es) COMPRESSED GAS, N.O.S. (Nitric Oxide, Nitrogen)

Class 2.2 Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1956

UN proper shipping name Transport hazard class(es) Compressed gas, n.o.s. (Nitric Oxide, Nitrogen)

Class 2.2 Subsidiary risk -

Packing group Not applicable.

Environmental hazards No ERG Code 2L

Special precautions for user

Other information

Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Cargo aircraft only

Allowed with restrictions.

Allowed with restrictions.

IMDG

UN number UN1956

UN proper shipping name COMPRESSED GAS, N.O.S. (NITRIC OXIDE, NITROGEN)

Transport hazard class(es)

Class 2.2 Subsidiary risk -

Packing group Not applicable.

Environmental hazards

Marine pollutant No EmS F-C, S-V

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: INOmax® SDS CANADA

SDS ID: NO123 Version #: 02 Revision date: 11-11-2016

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information

 Issue date
 09-13-2016

 Revision date
 11-11-2016

Version # 02

Disclaimer Mallinckrodt provides the information contained herein in good faith but makes no representation

as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT WILL NOT BE RESPONSIBLE FOR

DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Revision information Product and Company Identification: Synonyms

Composition / Information on Ingredients: Disclosure Overrides

Handling and storage: Conditions for safe storage, including any incompatibilities

Disposal considerations: Disposal instructions

HazReg Data: Pacific Rim